

COMMERCIAL PROPANE – BUTANE TYPE 40/60^{1,2}

USE: FUEL FOR HOUSEHOLD AND INDUSTRIAL USE

PROPERTY	MU	LIMITS		TEST METHOD
		Min.	Max.	
Composition:	% (m/m)			SR EN 27941:00 ³
C2-C3 saturated hydrocarbons		30	40	
C4 saturated hydrocarbons		balance		
C5 saturated hydrocarbons		-	1	
C2-C5 unsaturated hydrocarbons		-	55	
Density at 15 °C	Kg/m ³	to be reported		SR EN ISO 8973:02 (art.6.2) ³
Absolute vapour pressure at 40 °C	kPa	-	900	SR EN ISO 8973:02 (art.6.3) ³
Total sulphur (after odourisation)	mg/Nm ³	-	500	UOP 212-05 / SR EN ISO 6326-3:99

NOTES: 1) A sufficient amount of ethylmercaptan is added to the product to provide a specific odor, permitting the detection of the possible leaks 2) For every delivery, at client request, the product can be delivered unodorised 3) Accredited test by RENAR.

Quality control: control is done on lot.

Each batch will have max. one wagon for delivery in tank wagons or max. 5000 LPG bottles for delivery in LPG bottles. The lot will have product of same type.

For each batch must to check all quality coefficients provided in standard specification of the product/type.

The product must to comply with all provided characteristics. If not, the lot is rejected.

In case of litigation, quality control will be made on samples taken in accordance with sampling procedure and hold for this case.

Sampling procedure: ASTM D 1265-11(17) / SR EN ISO 4257:2002/AC:2007

Information on product classification, packing, labelling, handling, transport and storage: according to Safety Data Sheet S - 1.5.3 T.

The integrated Quality-Environment-Occupational Health and Safety Management System is certified by DNV-GL according to the following standards:

- ISO 9001
- ISO 14001
- BS OHSAS 18001

The test lab is accredited by RENAR, in compliance with SR EN ISO/CEI 17025.

© **ROMPETROL RAFINARE SA** Unauthorized reproduction by any mean, partial or total, is prohibited