

ROMPETROL RAFINARE SA – Vega Refinery Working Point COMPANY OF THE KMG INTERNATIONAL GROUP

Str, Valeni Nr. 146 Ploiesti , Jud. Prahova

Phone 0244 / 406.110(144;154) Fax: (40) 0244 / 406145, 0244/514469 www.rompetrol-rafinare.ro; www.rompetrol.com; email office.rafinare@rompetrol.com **SS 85**

Approval date: 23.11.2022

Revision 5

ROMPETROL SE 65/80

USES: INDUSTRY OF VARNISHES, PAINTS AND ADHESIVES, WASHING AGENTS AND DEGREASERS; GASOLINE MANUFACTURING; CHEMICAL INDUSTRY INTERMEDIARY; EXTRACTION SOLVENTS COMPONENT FOR OIL PRODUCTION AND POLYMERISATION PROCESSES

PROPERTY	MU	LIMITS		TEST METHOD*
		Min.	Max.	
Density at 15 °C	kg/m ³	-	720,0	SR EN ISO 12185
				SR EN ISO 3675
				ASTM D 4052
				ASTM D 1298
Distillation:				SR EN ISO 3405
- initial boiling point	$^{0}\mathrm{C}$	65,0	-	ASTM D 86
- 98% (v/v) distil at	0 C	-	80,0	
Benzene content	% (m/m)	-	0,02	Method GC
Aromatic hydrocarbons content	% (m/m)	-	0,05	Method GC
Saybolt colour	units	+30	-	ASTM D 156
Sulphur content	mg/kg	-	20,0	ASTM D 5453
Water and mechanical impurities		n	one	SS 85

^{*}For the mentioned test methods, the latest edition in force applies.

Determination of mechanical impurities and water

The sample for analysis is introduced into an eprouvette, with approximately 40 mm diameter and heated to 15....25°C.

Water and mechanical impurities are considered lack if the content of eprouvette is clear and do not have substances in suspension and no water decanted or other visible impurities at the bottom of the eprouvette.

Quality control: the control is done on lot (batch).

The batch size correspond to tank capacity, max 300 tones for delivery in trucks and tankers. The batch will consist of the same product type.

For each lot all quality characteristics provided in standard specification of the product must be checked.

Product must comply with all the specified characteristics. If not, the lot is rejected.

In case of litigation, quality control will be made on samples taken in accordance with sampling procedure and stored for this case.

Sampling procedure: SR EN ISO 3170-2004/C91:2005/ASTM D 4057-19

Information on product classification, packing, labelling, handling, transport and storage: according to Safety Data Sheet 67V.

The Integrated Management System is certified according to the following standards:

- ➤ ISO 9001
- ➤ ISO 14001
- > ISO 45001
- > ISO 50001

The test lab is accredited by RENAR, in compliance with SR EN ISO/CEI 17025.

© ROMPETROL RAFINARE SA Unauthorized reproduction by any mean, partial or total, is prohibited